

# SWITCH CATALOG



# Series T and TW

# MINIATURE INTEGRAL TOGGLE SWITCHES T 2150, TW 20,000, T 2660, TW 20,001

## Series T

SPECIFICATIONS			CURRENT RATINGS					
			28VDC			115VAC		
Catalog Number	Poles and Throw		Lamp Load (Amps)	Resistive Load (Amps)	Inductive Load (Amps)	Lamp Load (Amps)	Resistive Load (Amps)	Inductive Load (Amps) (.75 pf)
T1002	1 P.S.T.		5	20	15	3	10	10
T1003	1 P.D.T.		5	20	15	3	10	10
T2106	1 P.D.T.*		—	10	5	—	10	5
T2114	1 P.D.T.*		—	10	5	—	10	5
T2150	2 P.D.T.		—	3	1	—	3	1
T2153	2 P.D.T.		—	3	1	—	3	1
T3103	1 P.D.T.		—	5	3	—	5	3
T3113	1 P.D.T.		—	5	3	—	5	3

- Seal: Dust resistant
- Type of Operation: Maintained
- Electrical Life: 10,000 operations at 28VDC or 115VAC
- Mechanical Life: 20,000 operations
- Operating Temp. Range: -85°F to +160°F (-65°C to +71°C)

\*Two Circuit



T2114



T2153



T3113

## Series TW (Sealed)

SPECIFICATIONS			CURRENT RATINGS					
			28VDC			115VAC		
Catalog Number	MS Number <sup>①</sup>	Poles and Throw	Lamp Load (Amps)	Resistive Load (Amps)	Inductive Load (Amps)	Lamp Load (Amps)	Resistive Load (Amps)	Inductive Load (Amps) (.75 pf)
TW1002	—	1 P.S.T.	5	20	15	3	10	10
TW1003	—	1 P.D.T.	5	20	15	3	10	10
TW20000	—	2 P.D.T.	.5*	2	.5*	.1	.1	.1
TW20001	—	1 P.D.T.*	.5	2	.5	.5	.1	.1
TW20002	MS18151-1	1 P.D.T.	.5	1	.5	.1	.1	.1

- Seal: Dust proof (per MIL-S-83731)
- Type of Operation: Maintained
- Electrical Life: 20,000 operations at 28VDC or 115VAC
- Mechanical Life: 40,000 operations
- Operating Temp. Range: -40°F to +160°F (-40°C to +71°C)

① Qualified to MIL-DTL-83731

\*Two Circuit



TW20000



TW20002



TW20001



TW1003

NOTE: For specific drawing dimensions, contact factory at 1-800-955-7354.